


Blind Rivet Nuts (Inserts) Flat Head



Round shank
open type

① Steel zinc plated

M 3

D1 = 4,9 mm
D2 = 7 +/- 0,3 mm
k = 0,8 +/- 0,2 mm
L = +/- 0,2 mm
= 5 mm

M3 X 9,0 mm	0,5 - 2,0 mm	PYZ M3X9.0	250	2,0 Nm	1480 N	2500 N	
M3 X 11,0 mm	2,0 - 3,0 mm	PYZ M3X11.0	250	2,0 Nm	1480 N	2500 N	

M 4

D1 = 5,9 mm
D2 = 9 +/- 0,3 mm
k = 0,8 +/- 0,2 mm
L = +/- 0,2 mm
= 6 mm

M4 X 11,0 mm	0,3 - 2,0 mm	PYZ M4X11.0	250	4,5 Nm	3150 N	5850 N	
M4 X 13,0 mm	2,0 - 4,0 mm	PYZ M4X13.0	250				

M 5

D1 = 6,9 mm
D2 = 10 +/- 0,3 mm
k = 1,0 +/- 0,2 mm
L = +/- 0,2 mm
= 7 mm

M5 X 13,0 mm	0,5 - 2,5 mm	PYZ M5X13.0	250	5,4 Nm	4540 N	8860 N	
M5 X 15,0 mm	2,5 - 4,0 mm	PYZ M5X15.0	250				

M 6

D1 = 8,9 mm
D2 = 13 +/- 0,3 mm
k = 1,5 +/- 0,2 mm
L = +/- 0,2 mm
= 9 mm

M6 X 15,0 mm	0,5 - 3,0 mm	PYZ M6X15.0	250	17,9 Nm	6600 N	11430 N	
M6 X 17,0 mm	3,0 - 5,0 mm	PYZ M6X17.0	250				

M 8

D1 = 10,9 mm
D2 = 15 +/- 0,3 mm
k = 1,5 +/- 0,2 mm
L = +/- 0,2 mm
= 11 mm

M8 X 17,0 mm	0,5 - 3,0 mm	PYZ M8X17.0	250	32,0 Nm	9400 N	11950 N	
M8 X 19,0 mm	3,0 - 5,0 mm	PYZ M8X19.0	250				

M 10

D1 = 11,9 mm
D2 = 16 +/- 0,3 mm
k = 1,7 +/- 0,2 mm
L = +/- 0,2 mm
= 12 mm

M10 X 19,0 mm	1,0 - 3,0 mm	PYZ M10X19.0	250	55,0 Nm	10230 N	14300 N	
M10 X 21,0 mm	3,0 - 6,0 mm	PYZ M10X21.0	250				

Note: D1=12.9 mm also available upon request.

M 12

D1 = 14,9 mm
D2 = 20 +/- 0,3 mm
k = 1,9 +/- 0,2 mm
L = +/- 0,2 mm
= 15 mm

M12 X 22,0 mm	1,0 - 4,0 mm	PYZ M12X22.0	250	63,0 Nm	12520 N	28000 N	

WUXI ANSHIDA HARDWARE CO.,LTD.